

AquaRite® Flo Advanced



3 STANDARD **4th** 8000 HOURS




MORE THAN A SALT CHLORINATOR!

- **Salt chlorinator** combined with the control of pool equipments
- Wide range of Chlorine production, 8, 16, 22, 33, 50 gr/h and 2 items LS **covering the needs of all pools on the market**
- **Transparent cell** to enable a visual check of the production
- **Monitoring** of the filtration pump and the lighting
- No need of an additional transformer for the lighting, **the power is provided directly by the control unit for LED lights up to 50W**
- **pH, ORP kits** and temperature sensor available as an option
- Wifi and Ethernet optional connection kits available for a **remote control of the pool equipments**



INCLUDED



	Description	AQR-FLO-AD8	AQR-FLO-AD16	AQR-FLO-AD22	AQR-FLO-AD33	AQR-FLO-AD50	AQR-FLO-AD16LS	AQR-FLO-AD33LS	
AQUARITE® FLO ADVANCED	Production	8 g/h	16 g/h	22 g/h	33 g/h	50 g/h	-	-	
	Pool size up to	30 m³	75 m³	100 m³	150 m³	200 m³	60 m³	120 m³	
	Salt concentration	3 to 100 g/l						1.5 to 100 g/l	
	Display	Graphics display shows present production, cover, pH*, mV*, temp*							
	Protection	IP65							
	Superchlorination mode	●	●	●	●	●	●	●	●
	Manual adjustment of Cl	●	●	●	●	●	●	●	●
	Lighting management (supply up to 60W)	●	●	●	●	●	●	●	●
	Filter pump / VSTD pumps management	●	●	●	●	●	●	●	●
	Cover detection	●	●	●	●	●	●	●	●
	Smart mode: adjustment of Cl	●	●	●	●	●	●	●	●
	Mechanical Flow Switch	●	●	●	●	●	●	●	●
	Gas detector	●	●	●	●	No	●	●	●
	Self-cleaning	Programmable up to 999 min							
Alarms	Low salt / no flow / pH (60 minutes) / AL4 for cell configurable								
Control box dimensions	254 x 298 x 133								
AVAILABLE OPTIONS	pH kit	BKPER-OPTION-PH (plastic probe) / BSKBPER (plastic premium probe) / BGKBP (glass probe) - (1.5 L/h peristaltic pump)							
	Redox kit	E-OPTION-REDOX (plastic probe) / ES (plastic premium probe) / EG (glass probe)							
	Temperature kit	T-OPTION-TEMP (give access to smart filtration mode)							
	WiFi module	RS4WI-OPTION-W							
	Ethernet module	RS4NET-OPTION-L							



Flow switch included



pH kit as standard



Redox probe kit as standard



Temperature kit



WiFi module



Ethernet module

Complete your installation

Supply your filtration pump, salt chlorinator, heat pump, electric cleaner with **HPOWERPRO-A**

